

**Table 4 : Content, order and format of the product data sheet**

|     | <b>Parameter</b>   | <b>Parameter value and precision</b>                            |   |     | <b>Unit</b>     |
|-----|--|---|---|-----|-----------------|
| 1.  | Supplier's name or trade name  | Işı k Elektronik San.ve Tic. A.Ş                                |   |     |                 |
|     | Supplier's address   | Osmangazi Mah. Ahmet Yesevi<br>Cad.No:12 Esenyurt /<br>İstanbul |   |     |                 |
| 2.  | Model identifier   | ML24EW2000  |   |     |                 |
| 3.  | Energy efficiency class for Standard Dynamic Range (SDR)                                       | F   |   |     |                 |
| 4.  | Operating power demand for Standard Dynamic Range (SDR)  | 18,0  |   |     | W               |
| 5.  | Energy efficiency class for High Dynamic Range (HDR)   | -   |   |     |                 |
| 6.  | Operating power demand for High Dynamic Range (HDR)  | 0   |   |     | W               |
| 7.  | Off-position power demand  | 0   |   |     | W               |
| 8.  | Hibernation power demand   | 0,4   |   |     | W               |
| 9.  | Networked hibernation power demand   | 0   |   |     | W               |
| 10. | Electronic display type  | Television/ Monitor   |   |     |                 |
| 11. | Aspect ratio   | 16  | : | 9   | integer         |
| 12. | Screen resolution (pixels)   | 1366  | x | 768 | Pixels          |
| 13. | Screen diagonal  | 61  |   |     | Cm              |
| 14. | Screen diagonal  | 24  |   |     | İnches          |
| 15. | Visible screen area  | 15,4  |   |     | dm <sup>2</sup> |
| 16. | Used panel technology  | LED LCD   |   |     |                 |
| 17. | Available Automatic Brightness Control (ABC)   | No  |   |     |                 |
| 18. | Available voice recognition sensor   | No  |   |     |                 |
| 19. | Motion sensor available  | No  |   |     |                 |
| 20. | Image refresh frequency rate (default)   | 60  |   |     | Hz              |
| 21. | Minimum guaranteed availability of software and firmware updates (from the end of market sale) | 8   |   |     | years           |
| 22. | Minimum guaranteed availability of spare parts (from the end of market sale)                   | 7   |   |     | years           |
| 23. | Minimum warranty product support   | 2   |   |     | years           |
|     | Minimum duration of the general warranty offered by the supplier                               | 2   |   |     | years           |
| 24. | Power supply type  | Internal  |   |     |                 |
| 25. | External power supply (non-standardized and included in the product box)                       |   |   |     |                 |
|     | i, ii, iii   | Standard Name   | - |     |                 |
|     |  | Input Voltage   | - |     | V               |
|     |  | Output Voltage  | - |     | V               |
| 26. | Standardized external power supply (or appropriate one if not included in the product box)     | Standard Name   | - |     |                 |
|     |  | Required output voltage value                                   | - |     | V               |
|     |  | Required passing current value (minimum)                        | - |     | A               |
|     |  | Required current frequency                                      | - |     | Hz              |

\* bb, yy, zz codes are variables such as model name, cabin type, control type, color given according to customer demand. Codes can be a number 0-9 or a space or a symbol.